

Better Bilt Auger Anchors

**performance will vary depending on soil type and condition*

3A-A3s	sold in bundles of 10 augers per bundle
Single Flight Disc	3"
Auger Disc Thickness	11 gauge
Single Anchor Weight	1#
Shaft Length	15"
Finish	Lightly oiled
Shaft Dia.	1/2"
Approx Holding Cap.*	n/a
3A-A3	sold in bundles of 10 augers per bundle
Single Flight Disc	3"
Auger Disc Thickness	11 gauge
Single Anchor Weight	2#
Shaft Length	30"
Finish	Lightly oiled
Shaft Dia.	1/2"
Approx Holding Cap.*	1500#
3A-A4	sold in bundles of 10 augers per bundle
Single Flight Disc	4"
Auger Disc Thickness	9 gauge
Single Anchor Weight	3.5#
Shaft Length	30"
Finish	Lightly oiled
Shaft Dia.	1/2"
Approx Holding Cap.*	2500#
3A-A5	sold in bundles of 10 augers per bundle
Single Flight Disc	5"
Auger Disc Thickness	7 gauge
Single Anchor Weight	5#
Shaft Length	45"
Finish	Painted
Shaft Dia.	5/8"
Approx Holding Cap.*	3000#
3A-A6	sold in bundles of 10 augers per bundle
Single Flight Disc	6"
Auger Disc Thickness	6 gauge
Single Anchor Weight	7#
Shaft Length	45"
Finish	Painted
Shaft Dia.	11/16"
Approx Holding Cap.*	4000#

Notes: *Holding capacity is dependent on soil conditions and density. Special installation consideration must be taken in rocky soils. To achieve optimal holding capacity, auger anchors must be screwed deeply into the ground. After inserting a metal rod through the anchor eye, screw the anchor into the ground or use a power driver. Anchor can be embedded in concrete for a more permanent installation. Anchor eye openings can vary. Closed-end anchors are available on request. Call for a quotation.