

Better Bilt Earth Anchor Systems

Available in Multi-Packs and Single Tree Kits
Heavy Holding Capacity in 3 Sizes
Withstands High Winds and Severe Storms
1st Year Support for New Trees
Security Anchors for Outdoor Anti-Theft Protection
Simple Installation



Chisel tip for quick and easy installation



Earth Anchor Drive Rod
(400, 680, 880)



Earth Anchor Tree 880 Kit



Earth Anchor Palm Collar 680 Kit



3A-SEC680g
3A-SEC880g
Security Earth Anchor
680 and 880 sizes available



Earth Anchor Bulk Packs

Bulk packs of anchors w/ attached galvanized steel cable

Item	Qty	Length	Cable Dia.	Cap.*	Tree Size
3A-EC400	50	20"	1/16"	300 #	Up to 3"
3A-EC680	24	30"	1/8"	1100 #	Up to 6"
3A-EC880	12	42"	3/16"	3000 #	Up to 11"

Tree Anchor Kit

Kit consists of: 3 Anchors w/ attached galvanized steel cable, 3 tree collars and 6 cable clamps.
680 and 880 Kits include 3 integral turnbuckles.

Packaged ready for store display. Single kits sufficient for anchoring one tree or palm tree.

Item	Qty	Length	Cable Dia.	Cap.*	Tree Size
3A-EK400	1	12'	1/16"	300 #	Up to 3"
3A-EK680	1	13'	1/8"	1100 #	Up to 6"
3A-EK880	1	15'	3/16"	3000 #	Up to 11"

Palm Tree Collar Anchor Kit

Kit consists of: 3 Anchors w/ attached galvanized steel cable; 1 palm collar(webbing, ratchet, 3 triangle rings); 6 cable clamps and 3 integral turnbuckles.

Packaged ready for store display. Single kits sufficient for anchoring one tree or palm tree.

Item	Qty	Length	Cable Dia.	Cap.*	Tree Size
3A-EKPC680	1	13'	1/8"	1100 #	Up to 6"
3A-EKPC880	1	15'	3/16"	3000 #	Up to 11"

Security Earth Anchors

Single anchor w/ attached galvanized steel cable (large pull-through loop)

Item	Qty	Length	Cable Dia.	Cap.*
3A-SEC680g.125x54	1	54"	1/8"	1100 #
3A-SEC880g.187x60	1	60"	3/16"	3000 #

Earth Anchor Drive Rod

Item	Qty	Length
3A-ET400	1	24" x 1/2" steel rod (turned down to 1/4" at the drive end)
3A-ET680	1	36" x 1/2" steel rod
3A-ET880	1	46" x 7/8" steel rod

Installation Notes: Better Earth Anchors require a suitable size drive rod (available separately) for installation. A pre-drilled, 2" pilot hole is highly recommended prior to installing the 680 and 880 model anchors. The Earth Anchor is "set" for maximum holding capacity when it is perpendicular with the direction of the securing cable. Thread guying strap or cable through the galvanized cable loop and then complete your tie-down procedure.

**Anchor holding capacity is dependent on soil type and density*

To order call 1-800-544-4550
or visit us at: cartsandanchors.com
To see our full line of professional landscape products